

OCD25XSD ICD25XSD

Outdoor Day/Night 25X

Indoor Day/Night 25X

Product Features

- Day/Night Indoor & Outdoor PTZ
- 25X Zoom
- Sony EX-view Technology
- Low Light Operation
- Multi Protocol RS-485
- 24VAC Operation
- Advanced Privacy Masking
- Alarming
- Mounting Hardware Included



Specifications

PICKUP DEVICE	1/4" Sony Ex-view CCD
PIXELS	768 Hx494V (440000) NTSC
SCAN SYSTEM	15.625 KHz(H) 50 HZ(V)
HORIZONTAL RESOLUTION	480 TV Lines
SENSITIVITY	1.0 LUX (F1.4)
SIGNAL TO NOISE RATIO	>50 DB
SHUTTER	1/3-1/10000 sec
VIDEO OUTPUT	1.0 Vp-p/75 OHM
ZOOM RATIO	25X Optical (f=3.5-91mm F104-F3.0) 12X Digital (48 Wide/2.7 Tele)
FOCUS	Auto/Manual
IRIS	Auto/Manual
WHITE BLC, GAIN, AE CONTROL	Auto/Manual
POWER	24VAC +/- 10%
POWER CONSUMPTION	30VA (Heater & Fan)
OPERATING TEMPERATURE	0° C - 50° (Environmental Housing)
PAN SPEED	0-300°/Sec
TILT SPEED	0-60°/Sec
PRESETS	128 Presets (Max)
TOURS	6 Tours (Max)
WEIGHT	4 KG
RECOMMENDED CONTROLLER	SDKBD1 or SDKBD2

Specifications subject to change without notice.

2029 Opportunity Drive #3 Roseville, CA 95678
Toll free - (888) 771-4544 • Phone - (916) 787-1100 • Fax - (916) 787-1010
sales@armelectronics.com • www.armelectronics.com

**ARM
ELECTRONICS**