

# 2

## SPECIFICATIONS

Hard disk capacity	120 GB or 240 GB	
Television system	NTSC/PAL color signal standard (Switchable)	
Picture resolution	NTSC: 720 x 480 (Super/High), 352 x 480 (Standard) PAL: 720 x 576 (Super/High), 352 x 576 (Standard)	
Compression	MPEG2 (Video), MPEG1 Layer2 (Audio)	
Picture quality	3 levels (Super/High/Standard)	
Recording type	Frame	
Recording speed	1 (NTSC: 30 fps or PAL: 25 fps)	
Recording area	1	
Playback	Playback/Still/Search/Cue/Review/Frame advance/Slow	
Search mode	• Time/date search	Search by time and date
	• Alarm search	Search by alarm event list
Menu language	English/French/Spanish	
Clock settings	Month/Day/Year/Hours/Minutes/seconds	
Video input terminal	1.0 V p-p / 75 Ohm unbalanced (BNC)	
Video output terminal	1.0 V p-p / 75 Ohm unbalanced (BNC)	
Audio input terminal	-8 dbs, 27 k Ohm unbalanced (RCA pin jack)	
Audio output terminal	-8 dbs, 600 Ohm unbalanced (RCA pin jack)	
Microphone input terminal	-60 dBs, 10 k Ohm unbalanced (3.5 mm mini jack)	
LAN terminal	100BASE-TX/10BASE-T (RJ-45)	
USB terminal	For compact flash reader (Front)	
Control connector (Push lock)	RS-485 terminal	3 terminals: A/B/C
	Remote control input terminal	External switch connection or VA-RMN01 remote control
	Clock adjust output terminal	Normal 5 V, Low level active
	Non REC output terminal	Normal 5 V, Low level active
	Alarm input terminal	Normal open, Low level active
	Alarm reset input terminal	Normal open, Low level active
	Alarm output terminal	Normal 5 V, Low level active
	Warning output terminal	Open collector (500 mA), Low level active
Full out warning terminal	Open collector (50 mA), Low level active	
Power	120 V - 240 V AC, 50/60 Hz	
Current consumption	460 mA - 280 mA	
Operating environment	Temperature: 5 °C to 40 °C, Humidity: 10 % to 80 %	
Dimensions	210 (W) x 96 (H) x 391.5 (D) mm	
Weight	3.4 kg	

Note that product appearance and specifications are subject to change without prior notice.

